



Model	VPX	Pitch	Connector	Input	# Output	Wattage	Efficiency	High Altitude	Integrated Holdup
VPX55H-3	3U	0.8"	VITA 62	+28 VDC	6	500 Watts	89%	No	No
VPX55HS	3U	1.0"	VITA 62	+28 VDC	6	725 Watts	89%	No	No
VPX55-3HU	<u>3U</u>	0.8"	VITA 62	+28 VDC	N/A	400 Watts	N/A	Yes, optional	Used with VPX55H-3
VPX68	3U	1.0"	VITA 62	+28 VDC	6	400 Watts	92%	Yes, optional	Yes, optional
VPX57-31	3U	1.0"	VITA 62	+270 VDC	6	500 Watts	87%	Yes, optional	No
VPX57HS	3U	1.0"	VITA 62	+270 VDC	6	500 Watts	90%	Yes, optional	No
VPX56H-6	6U	1.0"	VITA 62	3Ø AC or +270 VDC	5	1,000 Watts	88%	No	No
VPX56H2-6	6U	1.0"	VITA 62	3Ø AC or +270 VDC	5	1,400 Watts	90%	Yes, optional	No



[Power Supply Selection Guide](#)

[All Power Supplies](#)

For more information Contact TPT KK

詳細はメール（sales.t@tptech.co.jp）でのお問い合わせもしくはホームページ（<http://www.tptech.co.jp/>）をご参照ください。

ティー・ピー・ティー株式会社

〒110-0008 東京都台東区池之端 1-6-13 （境会館 5F）

電話：03-5832-7350